

INTERAC-TIV KIOSK

INTERACT TO CONNECT



DAEZON

INTERAC-TIV KIOSK LCD SIGNAGE



Signage Focuses On Interaction With Audience

- A variety of screen size display (32" – 65") and viewing design
- Tempered glass chassis for highest security and steadiness
- High brightness to enhance the message effect
- Multi 10 Points Infra Red Touch Screen
- Integrated with high spec Windows 10 / Android 7.1
- Integrated Content Management System (CMS) for remote and multiple screens function

INTERAC-TIV KIOSK LCD SIGNAGE

Technical Specifications

| LCD Display | |
|--------------------|--|
| Panel Size | 32"/43"/49"/55"/65" |
| Resolution | 1920 x 1080 pixel (32-49")/ 3840 x 2160 pixel (55-65") |
| Brightness | 350/600 Nits |
| Contrast Ratio | 1400:1 |
| Viewing Angle | 178/178 |
| Aspect Ratio | 16:9 |
| LED Lifetime | ≥50,000 hours |
| Thickness | 19mm |
| Material | Tempered glass |
| Touch Screen | PCAP |
| Motherboard | |
| Operating System | Window 10 / Android 7.1 |
| CPU | Intel i5 4 th Gen / RK3288 |
| Memory | 4GB / 2GB |
| Storage | 128G SSD / 8G ROM |
| Network | WIFI, LAN |
| I/O Ports | USB 2.0 x2, Micro USB OTG x1, Stereo Mini Jack 3.5mm x1, RJ45 x1, HDMI Out x1 Standard MicroSD Card Slot x1 (Support Max 32G) |
| Speakers | 5W x2 |
| Kiosk Base | |
| Dimension | 110 x 52 x 56 cm |
| Weight | 40 kg |
| Environment | |
| Operating System | 0°C ~ 50°C |
| Storage System | -20°C ~ 60°C |
| Power | |
| Power Supply | 96~264 V |
| Rated Frequency | 50/60Hz |

INTERAC-TIV KIOSK LCD SIGNAGE

